

GASSONIC SURVEYOR

Ultrasonic Gas Leak Detector



Features

- Advanced stainless steel microphone technology
- Interface outputs include 4-20 mA analogue and alarm/fault relays
- Full AISI 316L stainless steel intrinsically safe housing enclosure
- Compatible with the Gassonic 1701 – Portable Test and Calibration Unit
- Wide dynamic range (44-104 dB)
- Local LED indicator
- Intrinsically safe

Benefits

- Instant detection of high-pressure gas leaks with coverage up to 20 meter in radius
- Industry standard output for remote alarm and fault indication
- Corrosion resistance in harsh environments
- Minimal maintenance and calibration requirements
- Retrofittable with Gassonic MM0100 installations
- Displays detector status
- Potential use in locations where power is restricted

Description

The Gassonic Surveyor is a non-concentration based gas detector used to detect leaks from high-pressure systems. Like other ultrasonic gas leak detectors, the Gassonic Surveyor responds to the airborne ultrasound generated from gas releases in open, well ventilated areas, where traditional methods of detection may be unsuitable or dependent on ventilation. Because the Gassonic Surveyor responds to the source of a gas release rather than the dispersed gas, it is unaffected by changing wind directions, gas dilution, and the direction of the gas leak. Further, with its maximum coverage radius of 20 meters, it can supervise a relatively large area with a single device.

The Gassonic Surveyor is immune to most false signals and can be configured to filter short timescale ultrasonic noise that can produce nuisance alarms. Frequencies below 25 kHz are removed by a high pass filter, effectively eliminating interference from audible and low frequency ultrasonic noise. At the same time, setting the alarm trigger level above the ultrasonic background noise ensures immunity to other noise sources. The result is a reliable method of detection, able to monitor environments with high levels of ultrasound such as turbine rooms and compressor stations.

Besides high-pressure gas applications in general, the Gassonic Surveyor is suited for installations restricted to low power (< 1 W).

Applications

- Offshore and Onshore Oil and Gas Installations
- Floating Production Storage and Offloading Vessels (FPSOs)
- Gas Compressor and Metering Stations
- Underground Gas Storage Facilities
- Petrochemical Processing Plants
- Hydrogen Storage Facilities
- LNG / LPG Trains
- LNG Re-gasification Plants
- Gas Turbine Power Plants
- Refineries

GASSONIC SURVEYOR

System Specifications

Detector Type:

Ultrasonic (acoustic) Gas Leak Detector

Detector Frequency Range:

25 kHz – 70 kHz

Dynamic Range:

44 – 104 dB

Detector Coverage*:

Very low noise areas (< 64 dB)

20 m radius at leak rate = 0.1 kg/s

12 m radius at leak rate = 0.03 kg/s

Low noise areas (< 74 dB)

12 m radius at leak rate = 0.1 kg/s

8 m radius at leak rate = 0.03 kg/s

High noise areas (< 84 dB)

8 m radius at leak rate = 0.1 kg/s

4 m radius at leak rate = 0.03 kg/s

Response Time: < 1 s (speed of sound)

Warranty: 2 years

Electrical Classification:

ATEX: II 2G EEx ia IIC T4

IECEX: EEx ia IIC T4

Approvals:

ATEX, IECEX, IEC 61508 certified to SIL 1 and 2**

Accessories:

Portable test and calibration unit, wind screen, sun shield, mounting bracket

* Reference gas: Methane. All dB levels are in the ultrasonic frequency range.

** It has a SIL 1 rating in simplex applications and SIL 2 in voted applications with "m+1" redundancy.

Environmental Specifications

Operating Temperature Range:

-40° F to 155° F (-40° C to 75° C)

Operating Humidity Range: 0 to 100% RH

Ingress Protection: IP66

Electrical Specifications

Input Power: 13 - 28 VDC 49 mW

Max. Power Consumption: 150 mA

Analog Signal:

0 mA: No power/Low supply voltage

3 mA: Unit inhibit

4 – 20 mA: 44 dB – 104 dB

Relays (option 1 or 2 operator selectable)

Option 1: Alarm relay

Option 2: Error relay

Cable Requirements:

Max. cable length between Surveyor and

power source @ 24 VDC (40 Ohm)

14 AWG – 7,900 ft (2,408 m)

Mechanical Specifications

Housing: Stainless steel AISI 316L

Dimensions: 7.17 x 5.71 in (182 x 145 mm)

Weight: 4.94 lbs (2.24 kg)

Conduit Entries: M20 x 1.5

Mounting: Stainless steel bracket

Specifications subject to change without notice.

Represented by:



www.gassonic.com
www.generalmonitors.com

Gassonic

Energivej 42 A

DK-2750 Ballerup

Denmark

Tel: +45-44-700-910

Fax: +45-44-700-911

Email: mail@gassonic.com

General Monitors

Lake Forest, CA

6776 Simpatica Circle

26776 Simpatica Circle

Lake Forest, California 92630

Tel: +1-949-581-4464

Fax: +1-949-581-1151

Email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive

Houston, Texas 77095

Tel: +1-281-855-6000

Fax: +1-281-855-3290

Email: gmhou@generalmonitors.com

Ireland

Ballybrit Business Park

Galway

Republic of Ireland

Tel: +353-91-751175

Fax: +353-91-751317

Email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road

#09-16 Mactech Building

Singapore 349307

Tel: +65-6-748-3488

Fax: +65-6-748-1911

Email: genmon@gmpacifica.com.sg

United Arab Emirates

Jebel Ali Free Zone Area,

JAFZA VIEW 18

3rd Floor 308

O: +971.4.8143814

F: +971.4.8857587

Email: Gmme@generalmonitors.ae

United Kingdom

Heather Close

Lyme Green Business Park

Macclesfield, Cheshire

United Kingdom, SK11 0LR

Tel: +44-1625-619583

Fax: +44-1625-619098

Email: info@generalmonitors.co.uk