



GENERAL MONITORS
Protection for life.

MODEL IR700

Infrared Carbon Dioxide Point Detector



Features

- No routine calibration required
- True fail-to-safe operation
- Multiple communication outputs
- Event logging
- Heated optics
- Dirty optics indication
- Wireless capability

Benefits

- Low maintenance
- True gas detection performance
- Provides complete status and control capability in the control room
- Stores fault, gas check, calibration and alarm event history
- Eliminates condensation
- Discriminates between true fault and cleaning requirements
- Compatible with ELPRO Technologies wireless devices

Description

The Model IR700 infrared (IR) point detector is a microprocessor-based carbon dioxide gas detector that continuously monitors CO₂ in ppm levels.

The IR700 detection principle is based on measuring the absorption of infrared radiation passing through a volume of gas using a dual beam, single detector method. The IR detector measures the intensity of two specific wavelengths, one at an absorption wavelength and another outside of the absorption wavelength. The gas concentration is determined by a comparison of these two values.

All of the IR700's electronics are contained within an explosion-proof housing allowing detector information to be processed at the point of detection. The IR700 provides 4-20 mA signal proportional to 0-100% full scale. In addition, the IR700 is equipped with Modbus or HART. Configurations with relays, Modbus, and HART are available.

The IR700 is calibrated at the factory and needs no routine field calibration. It requires only a periodic cleaning of the windows and re-zeroing to ensure dependable performance.

The IR700 IR point detector is available in either an aluminum or stainless steel housing and is designed for use in Class I, Div. 1, Groups B, C & D and Zone 1 areas for North America and Zones 1 and 21 internationally. The housing is IP66/Type 4X rated.

Applications

- Carbon Capture and Storage
- Enhanced Oil Recovery
- Chemical Plants
- Fertilizers
- Food & Beverage Bottling Plants
- Coal Gasification
- Metals
- Wastewater Treatment Facilities



MODEL IR700

System Specifications

Detector Type: Infrared absorption type

Measuring Range: 0 to 5000 ppm
Consult factory for other ranges

Gases: Carbon Dioxide (CO₂)

Detector Life: Greater than 5 years

Accuracy: ± 5% full scale ≤ 2500 ppm
± 10% full scale > 2500 ppm

Response Time: (with 100% FS gas applied)
T50 ≤ 4 s, T90 ≤ 8 s

Modes: Self test, normal operation, calibration (zero only or complete calibration)

Accessories: IR4000S CO₂ monitor, junction box, duct mount junction box, calibration cup, flow block, splash guard, rain guard, portable purge calibrator

Classification: Class I, Divisions 1 & 2, Groups B, C & D
(Ta = -40°C to +75°C)
Type 4X Ex d, IIB+H₂ T5 Gb, IP66
(Ta = -60°C to +75°C)
Ex t IIIC T100°C Db

Warranty: Two years

Approvals: CSA, ATEX, IECEx, CE Marking, HART Registered.

Environmental Specifications

Operating Temperature Range: -40°F to +122°F (-40°C to +50°C)

Storage Temperature Range: -76°F to +185°F (-60°C to +85°C)

Humidity: 10% to 95% RH, non-condensing

Mechanical Specifications

Diameter: 2.9 inches (74 mm)

Length: 8.87 inches (225 mm)

Weight: 3 lbs (1.35 kg) - aluminum
6 lbs (2.7 kg) - stainless steel

Mounting: 3/4" NPT

Housing: Aluminum 6061-T6 alloy or 316 stainless steel
Explosion Proof, IP66, Type 4x

Electrical Specifications

Input Power: 20-36 VDC
24 VDC @ 200 mA max.

Analog Signal: 4-20 mA (600 ohms max.)
Start up, Fault (non-HART)* 0 mA
Start up, Fault (HART)* 1.25 mA
Cal, Zero, Gas Check* 1.5 mA
Dirty Optics* 2.0 mA
0 to 100% LEL 4 to 20 mA (proportional)
Over-range 21.7 mA

** Under HART, the analog output minimum level can be configured as 3.5 mA or as stated above, depending on user selection.*

RS-485 Output: Modbus RTU, suitable for linking up to 128 units or up to 247 units with repeaters

Baud Rate: 2400, 4800, 9600, or 19200 BPS

HART: (Optional) HART 6, HART Device Description available. AMS Device Manager support

RFI/EMI Protection: Complies with EN 50270, EN 61000-6-4

Sample Cable Requirements: For cable resistance of 3 ohms/1,000 ft, maximum distance between IR4000S and power source @ 24 VDC:
14 AWG (2.5 mm²) - 3,330 ft (1,110 m)

For 16 AWG cable with cable resistance of 5 ohms/1,000 ft, maximum distance of analog output (100 ohms max.): 10,000 ft. (3,050 m)

Faults Monitored: Calibration errors, EPROM and EEPROM Checksum Errors, Optics Failure / Blockage; Low Supply Voltage

Wireless Communication: Available with ELPRO Technologies wireless devices

Standard Configuration: IR700-0-2-1-2-1
0-5000 ppm range, aluminum housing, splashguard w/screen, no junction box

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide

www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
email: gmhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8143814
Fax: +971-4-8857587
Email: gmme@generalmonitors.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
Email: info@generalmonitors.co.uk

Wuxi General Monitors

A joint venture
157 Hubin Road, C-11 1F
Wuxi, Jiangsu Province 214073
People's Republic of China
Tel: +86-510-8512 2222
Fax: +86-510-8512 8222
email: sales@wxglt.com